

# TP-4004D



## Specifications

Model	TP-4004D
Recording Inputs	4 Channel, Real Time recording
Recording Resolutions	D1, Half D1, CIF, All at 25 FPS per input
Video Compression	H.264
Audio Compression	G711A
Video Standards	PAL (625 Lines, 50 frames), NTSC (525 Lines, 60 frames)
Viewing Quality	PAL, D1 (704x576)
Playback Quality	PAL, CIF (352x288), D1 (704x576)
Motion Detection	396 Detection Zones, (22x18) Matrix
Recording Modes	Manual, Alarm Triggered, Dynamic Detection, Scheduled
Search Modes	Date & Time, Alarm event, Motion Detection
Video Output	BNC: VIDEO COMPOSITE, VGA OUTPUT
Audio Inputs	4 Channels
Alarm Inputs	4 inputs
Alarm Outputs	1 Normally Open contactors
Network	RJ-45, (10M/100M)
PTZ Control	1 port, RS485
USB Interface	3 ports, USB 2.0 Specification
Mobile Support	Iphone, Android, Symbian, Windows Mobile, BlackBerry
Hard Disk interface	1 SATA Port, up to 2 TB Capacity each.
IR Remote	Yes
Power Supply	12V DC
Dimension	310mm(W) x 220mm(D) x 42mm(H)
Operating Temperature	0°C ~ 55°C