

FULL BODY HIGH RESOLUTION LOW LIGHT



Function

- 1/3" 960H Sony EXview HAD II CCD
- 0.1Lux at F1.2
- High Resolution 700TV Line
- Built-in OSD Controller
- DNR(Digital Noise Reduction)
- Built-in ICR Filter(Optional)

Specification

DESCRIPTION	NTSC	PAL
Imaging Sensor	1/3" 960H Sony EXview HAD II CCD	
Effective Pixels	976(H) x 494(V)	976(H) x 582(V)
Scanning System	2:1 Interface	
Synchronization	Internal	
Horizontal Resolution	700TV Lines(Max)	
Video Output	CVBS : 1.0Vp-p, 75Ω composite	
S/N (Y Signal)	52dB (AGC off)	
Min. Illumination	0.1Lux at F1.2	
IRIS Adjustment	Manual / Auto	
Lens	C,CS Mount Lens	
Electronic Shutter	Auto / Manual (1/80~1/10,000sec)	Auto / Manual (1/50~1/10,000sec)
OSD Language	English / Japanese / German / French / Russian / Portuguese / Spanish	
Backlight Compensation	BLC / HLC / OFF	
White Balance	ATW / PUSH / USER1 / USER2 / ANTI CR / MANUAL / PUSH LOCK	
Auto Gain Control	Manual / Auto	
Day&Night	Color / Auto / B/W	
Privacy Masking	On/Off(4 zones)	
Mirror	On/Off	
Motion	On/Off	
ATR	On/Off	
DNR	Y/C Level Adjustment	
Input Voltage	DC 12V(±10%) / AC 24V Dual Voltage(Optional)	
Power Consumption	170mA(MAX) at DC 12V POWER	
	250mA(MAX) at AC 24V POWER	
Operating Temp./Hum.	-10°C~+50°C / 30% ~ 80% RH	
Storage Temp./Hum.	-20°C~+60°C / 20% ~ 80% RH	

Dimension

Unit : mm

