

Metallic Series

IR Rugged Metallic Tube

- Sliding Sunshield
- High Intensity IR
- Choice of Lenses
2.8-12mm / 6-50mm
- Day/Night Sensing
- OSD / Zoom / Focus via joystick
- Sealed Control Panel
- Installer's Video Jack



Ness Metallic Series Ultra High Resolution IR Cameras Built Tough - Look Sharp!

- ULTRA HIGH RESOLUTION 600TVL
 - 30m IR RANGE
- CHOICE OF VARIFOCAL LENSES
- OSD SETUP BY MINI JOYSTICK
 - DAY/NIGHT MODE
 - DIGITAL ZOOM

MODELS

104-352	IR RUGGED TUBE CAMERA METALLIC 2.8-12mm Lens
104-353	IR RUGGED TUBE CAMERA METALLIC 6-50mm Lens

INSTALLER FRIENDLY

Interchangeable extra deep base with conduit entry is supplied. For hard surface mounting.



SPECIFICATIONS

IMAGE SENSOR	1/3" Sony SuperHAD CCD / 2:1 Interlace
PIXELS	753(H) x 582(V)
HORIZONTAL RESOLUTION	600 TVL Colour mode / 700 TVL B/W mode
SYNCHRONIZATION	Internal
WHITE BALANCE	ATW1 / ATW2 / AWC / Manual
S/N RATIO	52dB (AGC Off, Weight On.)
ELECTRONIC SHUTTER	1/50~1/100,000 sec
MIN ILLUMINATION (IR LEDS OFF)	0.1 Lux @ F1.2 (Normal Mode) 0.0002 Lux @ F1.2 (Sens-Up x256)
IR LEDS / RANGE	48ea / 30m Max.
BACKLIGHT COMPENSATION	ON/OFF (Level setting)
CAMERA ID	ON/OFF (54 characters / 2 lines)
SENS UP	x2 ~ x256
AGC	LOW/HIGH/OFF Selectable
MOTION DETECTION	ON/OFF
PRIVACY FUNCTION	ON/OFF (8 Zones)
DIGITAL ZOOM	ON/OFF (x10)
DAY/NIGHT MODE	Colour/BW/AUTO/EXT
VIDEO OUTPUT	1.0Vp-p / 75 Ohms + installer's Video Out Port
LENS	f=2.8-12mm Aspheric AI Lens F1.2 (104-352) f=6-50mm Aspheric AI Lens F1.2 (104-353)
OPERATING VOLTAGE	12VDC / 24VAC
POWER CONSUMPTION	700mA max. @ 12VDC
DIMENSIONS / WEIGHT	116(W) x 140(H) x 254(D) mm / 1.7kg



CORPORATION

Innovative Electronic Solutions

www.ness.com.au

NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au